

Available Material Options			
Part #	Load bearing internal materials	Ball Material	Casing material & finish
9145	AISI 52100	AISI 52100	AISI 1012 -Zinc plated
9145-A	AISI 52100	AISI 440	AISI 1015 - Zinc plated
9145-SS	AISI 440	AISI 440	AISI 304 - Natural
9145-Z	AISI 440	AISI 440	AISI1015 - 'Electrostatic' finish~

~ Operating temperature -20°C + 125°C (continuous)

LOAD CAPACITY 1100kg

THIS DOCUMENT CONTAINS OMNITRACK LTD PROPRIETARY AND CONFIDENTIAL INFORMATION. IT IS LOANED FOR LIMITED PURPOSES ONLY AND REMAINS THE PROPERTY OF OMNITRACK LTD. IT MAY NOT BE REPRODUCED IN WHOLE OR PART OR DISCLOSED TO THIRD PARTIES WITHOUT THE PRIOR WRITTEN CONSENT OF OMNITRACK LTD. THE DOCUMENT IS TO BE RETURNED TO OMNITRACK LTD UPON REQUEST AND IN ALL EVENTS UPON COMPLETION OF THE USE FOR WHICH IT WAS LOANED.	
ALL DIMENSIONS SHOWN IN mm	<h1>Omnitrack Ltd</h1> <p>Station Road Industrial Estate, Woodchester, Gloucestershire, GL5 5EQ - UK</p> <p>Tel; +44 (0) 1453 8733 45 Fax; +44 (0) 1453 878 500 info@omnitrack.co.uk www.omnitrack.co.uk</p>
DRAWING No.	
9145	

Removable & reusable 'Spirolox' circlip allows cleaning/user servicing

