

Available Material Options				
Part #	Load bearing internal materials	Ball Material	Casing material & finish	Disc Springs
9540	AISI 52100	AISI 52100	AISI 1012 - Zinc plated	Carbon steel -
9540-A	AISI 52100	AISI 440	AISI 1015 - Zinc plated	Corrosion
9540-SS	AISI 440	AISI 440	AISI 304 - Natural	protection
9520-Z	AISI 440	AISI 440	AISI1015 - 'Electrostatic' finish~	lightly greased

~ Operating temperature -20°C + 125°C (continuous)

NOTES:

1. SUPPORTS A LOAD OF 450kg
2. 960kg LOAD AT MAX DEFLECTION.

THIS DOCUMENT CONTAINS OMNITRACK LTD PROPRIETARY AND CONFIDENTIAL INFORMATION. IT IS LOANED FOR LIMITED PURPOSES ONLY AND REMAINS THE PROPERTY OF OMNITRACK LTD. IT MAY NOT BE REPRODUCED IN WHOLE OR PART OR DISCLOSED TO THIRD PARTIES WITHOUT THE PRIOR WRITTEN CONSENT OF OMNITRACK LTD. THE DOCUMENT IS TO BE RETURNED TO OMNITRACK LTD UPON REQUEST AND IN ALL EVENTS UPON COMPLETION OF THE USE FOR WHICH IT WAS LOANED.	
ALL DIMENSIONS SHOWN IN mm	<p>Omnitrack Ltd</p> <p>Station Road Industrial Estate, Woodchester, Gloucestershire, GL5 5EQ - UK</p> <p>Tel; +44 (0) 1453 8733 45 Fax; +44 (0) 1453 878 500 info@omnitrack.co.uk www.omnitrack.co.uk</p>
DRAWING No. 9540	

